

Accessories and part options

TS-SD



Standard accessories

● **Power connector**



Model KCC-M4421-00

TS-S2
TS-SH
TS-SD

● **I/O cables (1m)**



Model KCC-M5362-00

TS-SD

Options

● **Support software TS-Manager**

P.688



Model KCA-M4966-0J (Japanese)
KCA-M4966-0E (English)

TS-S2
TS-SH
TS-X
TS-P
TS-SD

● **TS-Manager environment**

OS	Windows 2000, XP (32bit), Vista, 7, 8 / 8.1, 10 (Supported version: V.1.4.5 or later)
CPU	Exceeding the environment recommended by the OS being used
Memory	Exceeding the environment recommended by the OS being used
Hard disk	Vacant capacity of more than 20MB in the installation destination drive
Communication port	Serial (RS-232C), USB
Applicable controllers	TS series

Note. Windows is the registered trademark of US Microsoft Corporation in U.S.A. and other countries.

● **Data cables**

Communication cable for TS-Manager. Select from USB cable or D-sub cable.



Model USB type (5m) KCA-M538F-A0
D-Sub type (5m) KCA-M538F-01

Note. USB driver for communication cable can also be downloaded from our website.

TS-S2
TS-SH
TS-X
TS-P
TS-SD

● **Daisy chain and gateway connection cable**



Model KCA-M532L-00 (300mm)

TS-S2
TS-SH
TS-X
TS-P
TS-SD

Articulated robots
YA

Linear conveyor modules
LCM

Single-axis robots
CX

Motor-less single axis actuator
Robonity

Compact single-axis robots
TRANSEVO

Single-axis robots
FLIP-X

Linear motor single-axis robots
PHASER

Cartesian robots
XY-X

SCARA robots
YK-X

Pick & Place robots
YP-X

CLEAN

CONTROLLER

INFORMATION

Robot positioner

Pulse string driver

Robot controller

RCXIVY2+ Electric gripper

Option